

Product data sheet

Brass cable glands, metric

Item number: HS-K-MM




Illustrations may be similar

Material:	Brass nickel-plated
Sealing/Clamping insert::	Chloroprene, Prebunan, Polyamide 6
Connection thread:	M12 x 1,5; M16 x 1,5; M20 x 1,5; M25 x 1,5; M32 x 1,5; M40 x 1,5; M50 x 1,5; M63 x 1,5
Thread standard:	Metric, according to EN 60423
Clamping range mm:	3.0 - 6.5; 5.0 - 10.0; 6.0 - 12.0; 11.0 - 17.0; 15.0 - 21.0; 19.0 - 28.0; 34.0 - 44.0; 27.0 - 38.0
Thread length mm:	8.0; 14.0; 6.0; 7.0; 9.0
Wrench size mm:	SW 22; SW 27; SW 14; SW 20; SW 34; SW 43; SW 58; SW 64/68
Temperature range:	-40°C to +100°C
Protection class:	IP66 / IP68 / IP69
Test standard:	Integrated strain relief according to EN50262
Approvals:	UL, VDE
RoHS compliant:	Yes
Packaging unit:	50; 10; 25; 5

For individual advice, please feel free to contact us by email:

Subject to changes and errors.



Product link