


Product data sheet

Heat shrink tubing shrink ratio 2:1 RS2 Series Box

Item number: HS-RS2-BOX




Illustrations may be similar



Material:	Cross-linked polyolefin
Color:	black
Dim. D inches:	3/4; 1; 3/64; 1/16; 3/32; 1/8; 3/16; 1/4; 3/8; 1/2; 5/8
Ø before shrinkage / Ø after shrinkage:	1,2 mm / 0,6 mm; 1,6 mm / 0,8 mm; 2,4 mm / 1,2 mm; 3,2 mm / 1,6 mm; 4,8 mm / 2,4 mm; 6,4 mm / 3,2 mm; 9,5 mm / 4,8 mm; 12,7 mm / 6,4 mm; 16,0 mm / 8,0 mm; 19,1 mm / 9,5 mm; 25,4 mm / 12,7 mm
Wall thickness after complete shrinkage (mm):	0,22; 0,28; 0,35; 0,40; 0,50; 0,55; 0,60; 0,70; 0,80; 0,90
Min. shrink temperature:	70°C
Temperature for complete shrinkage:	125°C
Operating temperature:	-55°C bis + 125°C
Approval:	UL, CSA
RoHS III compliant:	Yes
Packaging unit in meters:	15; 12; 8; 5

For individual advice, please feel free to contact us by email:

Subject to changes and errors.



Product link