

Product data sheet

## Conduit fittings - HSPRO - Rigid

Item number: SVS-Starr




Illustrations may be similar

|                    |                                                                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material:          | Polyamide 6, UL94V0                                                                                                                                        |
| Color:             | light gray (RAL7035); gray (RAL7001); black (RAL9005)                                                                                                      |
| Thread:            | M12 x 1,5; M16 x 1,5; M20 x 1,5; M25 x 1,5; M32 x 1,5; M40 x 1,5; M50 x 1,5                                                                                |
| Hose AD mm:        | 23,0 - 26,5; 28,0 - 32,5; 31,0 - 33,5; 36,0 - 40,5; 38,5 - 44,0; 43,0 - 50,5; 48,0 - 53,5; 54,0 - 61,5; 10,0 - 15,0; 12,0 - 16,5; 14,0 - 18,5; 18,0 - 21,5 |
| Hose ID mm:        | 8,0; 10,0; 12,0; 16,0; 21,0; 25,0; 27,0; 32,0; 35,0; 40,0; 44,0; 50,0                                                                                      |
| ED mm:             | 6,0; 8,0; 10,0; 13,0; 18,0; 23,0; 24,0; 27,0; 30,0; 34,0; 39,0; 45,5                                                                                       |
| GL mm:             | 10; 12; 13; 14; 15; 20                                                                                                                                     |
| SW1 mm:            | 24; 26; 31; 36; 42; 45; 51; 54; 61; 66; 73                                                                                                                 |
| SW2 mm:            | 25; 28; 34; 40; 45; 48; 56; 60; 67; 72; 80                                                                                                                 |
| Temperature range: | -20°C to +80°C                                                                                                                                             |
| Protection class:  | IP65                                                                                                                                                       |
| RoHS compliant:    | Yes                                                                                                                                                        |
| Packaging unit:    | 50; 25; 10; 100                                                                                                                                            |

For individual advice, please feel free to contact us by email:

Subject to changes and errors.



Product link